



SIDE VIEW

END VIEW

TANK: CATEGORY 3. 3" 1000 AQUAKLEAR TANK 2 COMPARTMENT TANK REINFORCED WITH FIBRILLATED POLYPROPYLENE FIBER. 3" WALLS AND 3" BOTTOM. INLET AND OUTLET RESILIENT CONNECTORS PER ASTM-923-98. CONNECTORS MUST BE USED WITH APPROVED CLAMP. CONNECTOR WILL ACCEPT 4" PVC PIPE.

**LIDS: 3" LID WITH 1-22"/1-17" ROUND MANHOLE COVER
 8" LID WITH 1-22"/1-17" ROUND MANHOLE COVER
 LID IS REINFORCED WITH GRADE 60 REBAR.**

TANK & LIDS: 4000 PSI CONCRETE AT 28 DAYS

IMPRINTED ON INLET END OF TANK:

LEGEND: FSI 1000 STATE APPROVAL NUMBER: 01-011-AK10-C3

**WEIGHTS: TANK ONLY 6,760
 TANK & 3" LID 8,681
 TANK & 8" LID 11,883**

THIS SEWAGE TREATMENT RECEPTACLE HAS BEEN DESIGNED, CONSTRUCTED AND STRUCTURALLY TESTED IN ACCORDANCE WITH CHAPTER 64E-6.013, FLORIDA ADMINISTRATIVE CODE, (FAC) DATED APRIL 28, 2010.

DRAWING NOT TO SCALE

FLORIDA SEPTIC, INC

P.O. BOX 545
 HAWTHORNE, FLORIDA 32640
 (800) 940-8265

MODEL:

3' 1000 AQUAKLEAR TANK

REVISED:
 05/01/2011

APPROVAL DATE:
 AUGUST 18, 2008