



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

ACTIVE

Alachua

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL USE DATE	FAMILY
				WIDTH	LENGTH				
01-011-02D-C4	C4	4.00	52.30			750		5/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-02S-C4	C4	4.00	52.30			750		5/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-03D-C4	C4	6.00	55.25			1050		10/31/2001	
REMARKS:									
01-011-03S-C4	C4	6.00	55.25			1050		10/31/2001	
REMARKS:									
01-011-04D-C3	C3	2.50	43.50			900		1/31/2001	
REMARKS:									
01-011-06D-C4	C4	6.00	53.00			750		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-06S-C4	C4	6.00	53.00			750		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-07S-C3	C3	2.50	51.75			1050	B+ AT	6/11/2002	
REMARKS: Can be used to house Bio-Microbics MicroFAST 0.5 ATU when used with 350 gallon min. settling tank									
01-011-09D-C3	C3	2.50	50.00			1050		1/31/2001	
REMARKS: Houses Bionest BNC-400 ATU									
01-011-09S-C3	C3	2.50	50.00	62.3	101.3	1050	1,270	2/29/2008	
REMARKS:									
01-011-10D-C4	C4	4.00	55.00			1050		5/31/2001	
REMARKS:									
01-011-10S-C4	C4	4.00	55.00			1050		5/31/2001	
REMARKS:									
01-011-11D-C4	C4		44.00			1050	1,348	3/17/2003	
REMARKS: Houses Bionest BNC-400 ATU. Wall thickness can be either 4" or 6". AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-11S-C4	C4		44.00			1050	1,348	3/17/2003	
REMARKS: Wall thickness can be either 4" or 6". AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-12D-C3	C3	2.50	49.00			1200		12/14/2001	
REMARKS:									
01-011-12S-C3	C3	2.50	49.00			1200		12/14/2001	
REMARKS:									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL DATE	FAMILY
				WIDTH	LENGTH				
01-011-13D-C4	C4		52.00			1250	1,564	3/17/2003	
REMARKS: Houses Bionest BNC-500 ATU. Wall thickness can be either 4" or 6". AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-13S-C4	C4		52.00			1250	1,564	3/17/2003	
REMARKS: Wall thickness can be either 4" or 6". AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-16D-C3	C3	3.00	57.40			1350		5/31/2001	
REMARKS:									
01-011-16S-C3	C3	3.00	57.40			1350		5/31/2001	
REMARKS:									
01-011-19D-C4	C4	4.00	46.00			1350		7/30/2001	
REMARKS:									
01-011-19S-C4	C4	4.00	46.00			1350		7/30/2001	
REMARKS:									
01-011-20D-C3	C3	3.00	63.00			1500		5/31/2001	
REMARKS: Houses Bionest BNC-600 ATU.									
01-011-20S-C3	C3	3.00	63.00			1500		5/31/2001	
REMARKS:									
01-011-22D-C4	C4	4.00	41.50	75.2	151	1530	2,063	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-22S-C4	C4	4.00	41.50	75.2	151	1530	2,063	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-23D-C4	C4	4.00	53.00			1500		7/30/2001	
REMARKS: Houses Bionest BNC-600 ATU									
01-011-23S-C4	C4	4.00	53.00			1500		7/30/2001	
REMARKS:									
01-011-24D-C3	C3	3.00	44.00			1650		7/30/2001	
REMARKS:									
01-011-24S-C3	C3	3.00	44.00			1650		7/30/2001	
REMARKS:									
01-011-27D-C4	C4	6.00	53.00			1500		10/31/2001	
REMARKS: Houses Bionest BNC-600 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-27S-C4	C4	6.00	53.00			1500		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Alachua

Post Office Box 545
 Hawthorne, FL 32640

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL DATE	FAMILY
				WIDTH	LENGTH				
01-011-28D-C4	C4	6.00	41.50	79.2	155	1530	2,062	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-28S-C4	C4	6.00	41.50	79.2	155	1530	2,062	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-29D-C4	C4	4.00	44.00			1650		7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-29S-C4	C4	4.00	44.00			1650		7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-30D-C4	C4	6.00	44.00			1650		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-30S-C4	C4	6.00	44.00			1650		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-35D-C4	C4	4.00	50.50	76.3	152.8	1890	2,449	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-35S-C4	C4	4.00	50.50	76.3	152.8	1890	2,449	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-36D-C4	C4	6.00	50.50	80.3	156.8	1890	2,449	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-36S-C4	C4	6.00	50.50	80.3	156.8	1890	2,449	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-37D-C3	C3	3.00	53.00			2000		7/30/2001	
REMARKS: Houses Bionest BNC-750 ATU									
01-011-37S-C3	C3	3.00	53.00			2000		7/30/2001	
REMARKS:									
01-011-38D-C4	C4	4.00	53.00			2000		7/30/2001	
REMARKS: Houses Bionest BNC-750 ATU									
01-011-38S-C4	C4	4.00	53.00			2000		7/30/2001	
REMARKS:									
01-011-39D-C4	C4	6.00	53.00			2000		5/29/2002	
REMARKS: Houses Bionest BNC-750 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-39S-C4	C4	6.00	53.00			2000		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

ACTIVE

Alachua

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR WIDTH	TOP EXTERIOR LENGTH	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL USE DATE	FAMILY
01-011-40D-C3	C3	3.00	60.00			2300		7/30/2001	
REMARKS:									
01-011-40S-C3	C3	3.00	60.00			2300		7/30/2001	
REMARKS:									
01-011-41D-C4	C4	4.00	60.00			2300		7/30/2001	
REMARKS:									
01-011-41S-C4	C4	4.00	60.00			2300		7/30/2001	
REMARKS:									
01-011-42D-C4	C4	4.00	63.50	78	154.5	2445	3,021	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-42S-C4	C4	4.00	63.50	78	154.5	2445	3,021	4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.									
01-011-43D-C4	C4	4.00	66.00			2500		7/30/2001	
REMARKS: Houses Bionest BNC-1000 ATU									
01-011-43S-C4	C4	4.00	66.00			2500		7/30/2001	
REMARKS:									
01-011-44D-C4	C4	4.00	57.50	77.2	153.5	2180	2,752	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-44S-C4	C4	4.00	57.50	77.2	153.5	2180	2,752	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-45D-C4	C4	6.00	57.50	81.2	157.5	2180	2,752	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-45S-C4	C4	6.00	57.50	81.2	157.5	2180	2,752	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-46D-C4	C4	6.00	66.25			2500		5/29/2002	
REMARKS:									
01-011-46S-C4	C4	6.00	66.25			2500		5/29/2002	
REMARKS:									
01-011-47D-C4	C4	6.00	63.50	82	158.5	2445	3,023	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-47S-C4	C4	6.00	63.50	82	158.5	2445	3,023	4/9/2008	
REMARKS: 6" inlet and outlet									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Alachua

Post Office Box 545
 Hawthorne, FL 32640

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL	APPROVAL DATE	FAMILY
				WIDTH	LENGTH		GALLONS (Pump Tanks) USE		
01-011-49D-C4	C4	6.00	66.00			2500		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-49S-C4	C4	6.00	66.00			2500		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-51S-C4	C4	4.00	43.00	99.5	187.6	2825	3,733	4/9/2008	
REMARKS: 6" inlet and 2-4" outlets.									
01-011-52D-C4	C4	4.00	42.50	99.25	186.75	2800		8/14/2001	
REMARKS:									
01-011-52N-C4	C4	4.00	0.00	99.25	186.75	0		4/28/2013	
REMARKS: Modification of 01-011-52S-C4 for Florida Onsite Sewage Nitrogen Reduction Strategy Study. Stage 1 biofilter media tank: move outlet to within 5" of bottom of tank; add flow-through hole in second structural rib									
01-011-52S-C4	C4	4.00	42.50	99.25	186.75	2800		8/14/2001	
REMARKS:									
01-011-53D-C4	C4	6.00	42.50			2800		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-53S-C4	C4	6.00	42.50			2800		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-54D-C4	C4	4.00	43.00	99.5	187.6	2825	3,733	4/9/2008	
REMARKS: 6" inlet and outlet.									
01-011-54S-C4	C4	4.00	43.00	99.5	187.6	2825	3,733	4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.									
01-011-55D-C4	C4	6.00	43.00	103.5	191.6	2825	3,733	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-55S-C4	C4	6.00	43.00	103.5	191.6	2825	3,733	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-56D-C4	C4	4.00	45.25			3000		8/14/2001	
REMARKS:									
01-011-56S-C4	C4	4.00	45.25			3000		8/14/2001	
REMARKS:									
01-011-57D-C4	C4	6.00	45.50			3000		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-57S-C4	C4	6.00	45.50			3000		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR WIDTH	TOP EXTERIOR LENGTH	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL USE DATE	FAMILY
01-011-60D-C4	C4	6.00	60.00			2300		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-60S-C4	C4	6.00	60.00			2300		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-62D-C4	C4	4.00	47.00	99.75	188	3100	4,018	4/9/2008	
REMARKS: 6" inlet and outlet.									
01-011-62S-C4	C4	4.00	47.00	99.75	188	3100	4,018	4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.									
01-011-63D-C4	C4	6.00	47.00	103.7	192	3100	4,017	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-63S-C4	C4	6.00	47.00	103.7	192	3100	4,017	4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.									
01-011-64D-C4	C4	6.00	49.50	0	0	3300		11/8/2011	
REMARKS:									
01-011-64D-C3	C3	4.00	50.00			3300		8/14/2001	
REMARKS: Houses Bionest BNC-1250 ATU									
01-011-64S-C3	C3	4.00	50.00			3300		8/14/2001	
REMARKS:									
01-011-64S-C4	C4	4.00	49.50	99.75	188	3300	4,023	8/12/2008	
REMARKS:									
01-011-65D-C4	C4	6.00	49.50			3300		10/31/2001	
REMARKS: Houses Bionest BNC-1250 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-65S-C4	C4	6.00	49.50			3300		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-66D-C3	C3	4.00	63.25	100.1	188.4	3500	4,461	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-66S-C3	C3	4.00	63.25	100.1	188.4	3500	4,461	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-67D-C4	C4	6.00	53.25	104.1	192.4	3500	4,461	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-67S-C4	C4	6.00	53.25	104.1	192.4	3500	4,461	4/9/2008	
REMARKS: 6" inlet and outlet									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL DATE	FAMILY
				WIDTH	LENGTH				
01-011-68D-C3	C3	4.00	54.00			3700		8/14/2001	
REMARKS: Houses Bionest BNC-1500 ATU									
01-011-68S-C3	C3	4.00	54.00			3700		8/14/2001	
REMARKS:									
01-011-69D-C4	C4	6.00	55.00			3700		5/29/2002	
REMARKS: Houses Bionest BNC-1500 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-69S-C4	C4	6.00	55.00			3700		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-70D-C3	C3	4.00	62.00	101.1	189.5	4150	5,109	4/9/2008	
REMARKS: 6" inlet and outlet.									
01-011-70S-C3	C3	4.00	62.00	101.1	189.5	4150	5,109	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-71D-C4	C4	6.00	62.00	105.1	193.4	4150	5,107	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-71S-C4	C4	6.00	62.00	105.1	193.4	4150	5,107	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-72D-C3	C3	4.00	64.50			4300		8/14/2001	
REMARKS:									
01-011-72S-C3	C3	4.00	64.50			4300		8/14/2001	
REMARKS:									
01-011-73D-C4	C4	6.00	64.50			4300		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-73S-C4	C4	6.00	64.50			4300		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-74D-C4	C4	6.00	72.80	109	194.7	4900	5,910	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-74S-C4	C4	6.00	72.80	109	194.7	4900	5,910	4/9/2008	
REMARKS: 6" inlet and outlet									
01-011-76D-C3	C3	4.00	72.00			5000		8/14/2001	
REMARKS:									
01-011-76S-C3	C3	4.00	72.00			5000		8/14/2001	
REMARKS:									



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

ACTIVE

Alachua

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR WIDTH	TOP EXTERIOR LENGTH	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	USE	APPROVAL DATE	FAMILY
01-011-77D-C4	C4	6.00	73.50	106	194.75	5000		B	5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-77S-C4	C4	6.00	73.50	106	194.75	5000		B	5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-78D-C3	C3	4.00	72.80	102	190.75	4900	5,916		4/9/2008	
REMARKS: 6" inlet and outlet										
01-011-78S-C3	C3	4.00	72.80	102	190.75	4900	5,916		4/9/2008	
REMARKS: 6" inlet and outlet										
01-011-78S-C3	C3	4.00	72.80	102	190.75	4900	5,916		4/9/2008	
REMARKS: 6" inlet and outlet										
01-011-90D-C4	C4	4.00	43.00			1250			7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-90S-C4	C4	4.00	43.00			1250			7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-91D-C4	C4	6.00	43.00			1250			10/31/2001	
REMARKS:										
01-011-91S-C4	C4	6.00	43.00			1250			10/31/2001	
REMARKS:										
01-011-92D-C4	C4	6.00	46.00			1350			10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-92S-C4	C4	6.00	46.00			1350			10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-93S-C4	C4	4.00	42.00			300			12/14/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-94-C4	C4	4.00	34.75			300	358		6/8/2005	
REMARKS: Siphon tank.										
01-011-96S-C4	C4	3.00	42.00	45.75	53.75	300	370		1/31/2001	
REMARKS:										
01-011-97S-C4	C4	3.00	42.00	62.25	62.35	525	630		1/31/2001	
REMARKS:										
01-011-AK10-C3	C3	3.00	56.50	62	119	1342	1,583		8/12/2008	
REMARKS: Houses AquaKlear AK1000C 1000 gallon per day ATU; two notches for 1/2" airline on inlet side										



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

ACTIVE

Alachua

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	APPROVAL USE DATE	FAMILY
				WIDTH	LENGTH				
01-011-AK5-C4	C4	3.00	49.50	50	89.5	640	773 ATU	12/14/2005	
REMARKS: Houses AquaKlear AK500C 500 gpd ATU; two notches for 1/2" airline on inlet side									
01-011-AK5B-C3	C3	3.00	50.50	81.38	139.5	1875	ATU	8/27/2007	
REMARKS: Houses AquaKlear AK5B3 500 gpd ATU unit, which contains an AK500C unit with pretreatment and dosing compartments. Two section lid.									
01-011-AK8-C3	C3	3.00	57.50	57	103	1020	1,193 ATU	12/14/2005	
REMARKS: Used to house AquaKlear AK800C gallon per day ATU; two notches for 1/2" airline on inlet side.									
01-011-BM1-C3	C3	3.00	45.00			1100	1,479 ATU	10/31/2003	
REMARKS: Used to house Bio-Microbics MicroFAST 0.5FS ATU									
01-011-BM10-C4	C4	6.00	66.00			2400		3/28/2012	
REMARKS: Converted 02-05-2012. Houses Bio-Microbics MicroFAST 1.5 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-BM11-C4	C4	6.00	66.00	106	194.75	4500	5,909 ATU	3/28/2012	
REMARKS: Used to house Bio-Microbics MicroFAST 3.0F and 3.0FS ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"									
01-011-BM12-C4	C4	6.00	65.00	106	194.75	4400	ATU	3/28/2012	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48". Used to house Bio-Microbics MicroFAST 4.5F ATU									
01-011-BM2-C4	C4	4.00	53.00			1500	1,919 ATU	10/31/2003	
REMARKS: Used to house Bio-Microbics MicroFAST 0.5FS, 0.75FS, and 0.9FS ATU									
01-011-BM3-C4	C4	4.00	57.00			2150	2,752 ATU	10/31/2003	
REMARKS: Used to house Bio-Microbics MicroFAST 1.5FS ATU									
01-011-BM4-C3	C3	3.00	43.00			1600	2,433 ATU	10/31/2003	
REMARKS: Used to house Bio-Microbics MicroFAST 0.5F, 0.75F, and 0.9F ATU									
01-011-BM5-C3	C3	6.00	66.00			4500	5,909 ATU	10/31/2003	
REMARKS: Used to house Bio-Microbics MicroFAST 3.0F and 3.0FS ATU									
01-011-BM6-C3	C3	4.00	65.00	102	190.75	4400	5,913 ATU	2/17/2004	
REMARKS: Used to house Bio-Microbics MicroFAST 4.5F ATU									
01-011-BM7-C4	C4	4.00	63.00	78	154.5	2400	3,021 ATU	9/13/2007	
REMARKS: Used to house Bio-Microbics MicroFAST 1.5F or S ATU. Inlet and/or outlet can be 4" or 6".									
01-011-BM8-C4	C4	4.00	44.00			1650		7/30/2001	
REMARKS: (01-011-29S-C4 converted to ATU tank, 02-05-2012) Used to house Bio-Microbics MicroFAST 1.5 ATU with 750 gallon pretreatment tank.									
01-011-BM8-C4	C4	6.00	63.00	78	154.5	2400	3,021	3/1/2112	
REMARKS:									



DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 7/30/2013

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)	USE	APPROVAL	
				WIDTH	LENGTH				DATE	FAMILY
01-011-BM9-C4	C4	6.00	53.00			1500			10/31/2001	
REMARKS: Converted 01-011-27D-C4, to house Bio-Microbics MicroFAST .5, .75, and .9 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"										
01-011-CS1-C4	C4	3.00	55.00	84	155		2,232		5/12/2010	
REMARKS: Used to house the Clearstream model 600NC3T treatment unit										
01-011-FT1-C3	C3	3.00	30.50	73.2	149.1	1150	1,505	Filter	7/29/2005	
REMARKS: Filter media tank w/65 sq ft surface area										
01-011-FT2-C4	C4	4.00	29.50	98.25	186.5	1950	2,648	Filter	1/3/2007	
REMARKS: Filter media tank w/112 sq ft surface area										
01-011-FT3-C4	C4	4.00	30.50	0	0	1150	1,505	filter m	4/30/2007	
REMARKS: Filter media tank w/65 sq ft surface area-corrected category to C4 on 01-26-2012										