



DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

Table with columns: TANK NUMBER, CATEGORY, WALL THICKNESS, LIQUID DEPTH, TOP EXTERIOR WIDTH, TOP EXTERIOR LENGTH, IN-OUT DROP, EFFECTIVE GALLONS, TOTAL GALLONS (Pump Tanks), USE, APPROVAL DATE, FAMILY. Includes multiple rows of septic tank data with associated remarks.



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL USE	APPROVAL DATE	FAMILY
				WIDTH	LENGTH							
01-011-19S-C4	C4	4.00	46.00	68.5	132.13	2.5	1350	1,650			7/30/2001	
REMARKS:												
01-011-20D-C3	C3	3.00	62.50	61	129.5	2.5	1500	1,700	B, GI		5/31/2001	
REMARKS: Houses Bionest BNC-600 ATU.												
01-011-20P-C3	C3	3.00	62.50	61	129.5	1	1500	1,700	D		2/28/2011	
REMARKS: lowered pass-through hole for dosing tank												
01-011-20S-C3	C3	3.00	62.50	61	129.5	2.5	1500	1,700			5/31/2001	
REMARKS:												
01-011-22D-C4	C4	4.00	42.00	75.25	151.5	2.5	1530	2,063	B, GI		4/9/2008	
REMARKS: 6" inlet and outlet												
01-011-22P-C4	C4	4.00	42.00	75.25	151.5	2.5	1530	2,063	D		2/28/2011	
REMARKS: 6" inlet and outlet; lowered pass-through hole for dosing tank												
01-011-22S-C4	C4	4.00	41.50	75.25	151.5	2.5	1530	2,063			4/9/2008	
REMARKS: 6" inlet and outlet												
01-011-23D-C4	C4	4.00	53.00	69	133	2.5	1500	1,800	B, GI		7/30/2001	
REMARKS: Houses Bionest BNC-600 ATU												
01-011-23P-C4	C4	4.00	53.00	69	133	2.5	1500	1,800	D		2/28/2011	
REMARKS: lowered pass-through hole for dosing tank												
01-011-23S-C4	C4	4.00	53.00	69	133	2.5	1500	1,800			7/30/2001	
REMARKS:												
01-011-24D-C3	C3	3.00	44.00	73.25	149.25	2.5	1650	1,900	B, GI		7/30/2001	
REMARKS:												
01-011-24P-C3	C3	3.00	44.00	73.25	149.25	2.5	1650	1,900	D		2/28/2011	
REMARKS: lowered pass-through hole for dosing tank												
01-011-24S-C3	C3	3.00	44.00	73.25	149.25	2.5	1650	1,900			7/30/2001	
REMARKS:												
01-011-27D-C4	C4	6.00	53.00	73	137	2.5	1500	1,918	B, GI		10/31/2001	
REMARKS: Houses Bionest BNC-600 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"												
01-011-27P-C4	C4	6.00	53.00	73	137	2.5	1500	1,918	D		2/28/2011	
REMARKS: ASSHTO HS20 traffic loading rated when buried between 18" to 48"												
01-011-27S-C4	C4	6.00	53.00	73	137	2.5	1500	1,918			10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"												
01-011-28D-C4	C4	6.00	41.50	79.25	155.5	2.5	1530	2,062	B, GI		4/9/2008	
REMARKS: 6" inlet and outlet												



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL USE DATE	FAMILY
				WIDTH	LENGTH						
01-011-28P-C4	C4	6.00	41.50	79.5	155.5	2.5	1530	2,062	D	2/28/2011	
REMARKS: 6" inlet and outlet											
01-011-28S-C4	C4	6.00	41.50	79.25	155.5	2.5	1530	2,062		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-29D-C4	C4	4.00	44.00	75.25	151.5	2.5	1650	2,000	B, GI	7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-29N-C4	C4	4.00	4.00	75.25	151.5	42.5	0	2,000		10/3/2013	
REMARKS: Modification of 01-011-29S-C4 for Florida Onsite Sewage Nitrogen Reduction Strategy Study. Media tank: liquid level =4"; add flow-through hole in second structural rib. AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-29P-C4	C4	4.00	44.00	75.25	151.5	2.5	1650	2,000	D	2/28/2011	
REMARKS: lowered pass-through hole for dosing tank; AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-29S-C4	C4	4.00	44.00	75.25	151.5	2.5	1650	2,000	B	7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-30D-C4	C4	6.00	44.00	79.25	155.5	2.5	1650	2,000	B, GI	5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-30P-C4	C4	5.00	44.00	79.25	155.5	2.5	1650	2,000	D	2/28/2011	
REMARKS: ASSHTO HS20 traffic rating when buried between 18" to 48"											
01-011-30S-C4	C4	6.00	44.00	19.25	155.5	2.5	1650	2,000		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-35D-C4	C4	4.00	50.50	76.25	152.75	2.5	1890	2,449	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-35P-C4	C4	4.00	50.50	76.25	152.75	2.5	1890	2,449	D	2/28/2011	
REMARKS: 6" inlet and outlet; lowered pass-through hole for dosing tank											
01-011-35S-C4	C4	4.00	50.50	76.25	152.75	2.5	1890	2,449		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-36D-C4	C4	6.00	50.50	80.25	156.75	2.5	1890	2,449		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-36P-C4	C4	6.00	50.50	80.25	156.75	2.5	1890	2,449	D	2/28/2011	
REMARKS: 6" INLET AND OUTLET											
01-011-36S-C4	C4	6.00	50.50	80.25	156.75	2.5	1890	2,449		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-37D-C3	C3	3.00	53.00	74.25	150.5	2.5	2000	2,300	B	7/30/2001	
REMARKS: Houses Bionest BNC-750 ATU											
01-011-37P-C3	C3	3.00	53.00	74.25	150.5	1	2000	2,300	D	2/28/2011	
REMARKS: lowered pass-through hole for dosing tank											



DEPARTMENT OF HEALTH
STATE HEALTH OFFICE
SEPTIC TANK DESIGNATED APPROVAL NUMBERS
SEPTIC TANK MANUFACTURERS
run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL USE	APPROVAL DATE	FAMILY
				WIDTH	LENGTH							
01-011-37S-C3	C3	3.00	53.00	74.25	150.5	2.5	2000	2,300			7/30/2001	
REMARKS:												
01-011-38D-C4	C4	4.00	53.00	76.25	152.75	2.5	2000	2,400	B		7/30/2001	
REMARKS: Houses Bionest BNC-750 ATU												
01-011-38P-C4	C4	4.00	53.00	76.25	152.75	2.5	2000	2,400	D		2/28/2011	
REMARKS: lowered pass-through hole for dosing tank												
01-011-38S-C4	C4	4.00	53.00	76.25	152.75	2.5	2000	2,400			7/30/2001	
REMARKS:												
01-011-39D-C4	C4	6.00	53.00	80.25	156.75	2.5	2000	2,400	B		5/29/2002	
REMARKS: Houses Bionest BNC-750 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"												
01-011-39P-C4	C4	6.00	53.00	80.25	156.75	2.5	2000	2,400	D		2/28/2011	
REMARKS: ASSHTO HS20 traffic rating when buried between 18" to 48"												
01-011-39S-C4	C4	6.00	53.00	80.25	156.75	2.5	2000	2,400			5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"												
01-011-40D-C3	C3	3.00	60.00	75.25	151.25	2.5	2300	2,600	B		7/30/2001	
REMARKS:												
01-011-40P-C3	C3	3.00	60.00	75.25	151.25	2.5	2300	2,600	D		2/28/2011	
REMARKS: lowered pass-through hole for dosing tank												
01-011-40S-C3	C3	3.00	60.00	75.25	151.25	2.5	2300	2,600			7/30/2001	
REMARKS:												
01-011-41D-C4	C4	4.00	60.00	77.25	153.5	2.5	2300	2,700	B		7/30/2001	
REMARKS:												
01-011-41P-C4	C4	4.00	60.00	77.25	153.5	2.5	2300	2,700	D		2/28/2011	
REMARKS: lowered pass-through hole for dosing tank												
01-011-41S-C4	C4	4.00	60.00	77.25	153.5	2.5	2300	2,700			7/30/2001	
REMARKS:												
01-011-42D-C4	C4	4.00	63.50	78	154.5	2.5	2445	3,021	B		4/9/2008	
REMARKS: 6" inlet and outlet												
01-011-42P-C4	C4	4.00	63.50	78	154.5	2.5	2445	3,021	D		2/28/2011	
REMARKS: 6" inlet and outlet; lowered pass-through hole for dosing tank												
01-011-42S-C4	C4	4.00	63.50	78	154.5	2.5	2445	3,021			4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.												
01-011-43D-C4	C4	4.00	65.50	78	154.5	2.5	2500	2,900			7/30/2001	
REMARKS: Houses Bionest BNC-1000 ATU												



DEPARTMENT OF HEALTH
STATE HEALTH OFFICE
SEPTIC TANK DESIGNATED APPROVAL NUMBERS
SEPTIC TANK MANUFACTURERS
run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL DATE	FAMILY
				WIDTH	LENGTH			USE			
01-011-43P-C4	C4	4.00	65.50	78	154.5	2.5	2500	2,900	D	2/28/2011	
REMARKS: lowered pass-through hole for dosing tank											
01-011-43S-C4	C4	4.00	65.50	78	154.5	2.5	2500	2,900		7/30/2001	
REMARKS:											
01-011-44D-C4	C4	4.00	57.50	77.25	153.5	2.5	2180	2,752	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-44P-C4	C4	4.00	57.50	77.25	153.5	2.5	2180	2,752	D	2/28/2011	
REMARKS: 6" inlet and outlet; lowered pass-through hole for dosing tank											
01-011-44S-C4	C4	4.00	57.50	77.25	153.5	2.5	2180	2,752		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-45D-C4	C4	6.00	57.50	81.25	157.5	2.5	2180	2,752	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-45P-C4	C4	6.00	57.75	81.25	157.5	2.5	2180	2,752	D	2/28/2011	
REMARKS: 6" inch inlet and outlet											
01-011-45S-C4	C4	6.00	57.50	81.25	157.5	2.5	2180	2,752		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-47D-C4	C4	6.00	63.50	82	158.5	2.5	2445	3,023	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-47S-C4	C4	6.00	63.50	82	158.5	2.5	2445	3,023		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-49D-C4	C4	6.00	65.50	82	158.5	2.5	2500	3,023		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-49P-C4	C4	6.00	65.50	82	158.5	2.5	2500	3,023	D	2/28/2011	
REMARKS: AASHTO HS20 traffic rating when buried between 18" to 48"											
01-011-49S-C4	C4	6.00	65.50	82	158.5	2.5	2500	3,023		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-52D-C4	C4	4.00	42.50	99.25	186.75	2.5	2800	3,518	B	8/14/2001	
REMARKS:											
01-011-52N-C4	C4	4.00	0.00	99.25	186.75	40	0	3,518		4/28/2013	
REMARKS: Modification of 01-011-52S-C4 for Florida Onsite Sewage Nitrogen Reduction Strategy Study. Stage 1 biofilter media tank: move outlet to within 5" of bottom of tank; add flow-through hole in second structural rib											
01-011-52P-C4	C4	4.00	42.50	99.25	186.75	2.5	2800	3,518	D	2/28/2011	
REMARKS: lowered pass-through hole for dosing tank											
01-011-52S-C4	C4	4.00	42.50	99.25	186.75	2.5	2800	3,518		8/14/2001	
REMARKS:											



DEPARTMENT OF HEALTH
STATE HEALTH OFFICE
SEPTIC TANK DESIGNATED APPROVAL NUMBERS
SEPTIC TANK MANUFACTURERS
run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL	
				WIDTH	LENGTH			USE	DATE	FAMILY	
01-011-53D-C4	C4	6.00	42.50	103.3	190.75	2.5	2800	3,518	B	10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-53P-C4	C4	6.00	42.50	103.3	190.75	2.5	2800	3,518	D	2/28/2011	
REMARKS: ASSHTO HS20 traffic rating when buried between 18" to 48"											
01-011-53S-C4	C4	6.00	42.50	103.3	190.75	2.5	2800	3,518		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-54D-C4	C4	4.00	43.00	99.5	187.63	2.5	2825	3,733	B	4/9/2008	
REMARKS: 6" inlet and outlet.											
01-011-54P-C4	C4	4.00	43.00	99.5	187.63	2.5	2825	3,733	D	2/28/2011	
REMARKS: 6" inlet and outlet; lowered pass-through hole for dosing tank											
01-011-54S-C4	C4	4.00	43.00	99.5	187.63	2.5	2825	3,733		4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.											
01-011-55D-C4	C4	6.00	43.00	103.5	191.63	2.5	2825	3,733	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-55P-C4	C4	6.00	43.00	103.5	191.63	2.5	2825	3,733	D	2/28/2011	
REMARKS: 6" inlet and outlet; lowered pass-through hole for dosing tank											
01-011-55S-C4	C4	6.00	43.00	103.5	191.63	2.5	2825	3,733		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-56D-C4	C4	4.00	45.50	99.5	187.63	2.5	3000	3,733	B	8/14/2001	
REMARKS:											
01-011-56P-C4	C4	4.00	45.50	99.5	187.63	2.5	3000	3,733	D	2/28/2011	
REMARKS: lowered pass-through hole for dosing tank											
01-011-56S-C4	C4	4.00	45.50	99.5	187.63	2.5	3000	3,733		8/14/2001	
REMARKS:											
01-011-57D-C4	C4	6.00	45.50	103.5	191.63	2.5	3000	3,733	B	10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-57P-C4	C4	6.00	45.50	103.5	191.63	2.5	3000	3,733	D	2/28/2011	
REMARKS: AASHTO HS20 traffic rating when buried between 18" to 48"											
01-011-57S-C4	C4	6.00	45.50	103.5	191.63	2.5	3000	3,733		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-60D-C4	C4	6.00	60.00	81.25	157	2.5	2300	2,752	B	5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-60P-C4	C4	6.00	60.00	81.25	157	2.5	2300	2,752	D	2/28/2011	
REMARKS: AASHTO HS20 traffic rating when buried between 18" to 48"											



DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL DATE	FAMILY
				WIDTH	LENGTH			USE			
01-011-60S-C4	C4	6.00	60.00	81.25	157	2.5	2300	2,752		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-62D-C4	C4	4.00	47.00	99.75	188	2.5	3100	4,023	B	4/9/2008	
REMARKS: 6" inlet and outlet.											
01-011-62P-C4	C4	4.00	47.00	97.75	188	2.5	3100	4,023		2/28/2011	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.											
01-011-62S-C4	C4	4.00	47.00	99.75	188	2.5	3100	4,023		4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.											
01-011-63D-C4	C4	6.00	47.00	103.8	192	2.5	3100	4,023	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-63P-C4	C4	6.00	47.00	103.8	192	2.5	3100	4,023	D	2/28/2011	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.											
01-011-63S-C4	C4	6.00	47.00	103.8	192	2.5	3100	4,023		4/9/2008	
REMARKS: 6" inlet and outlet or 6" inlet and 2-4" outlets.											
01-011-64D-C4	C4	4.00	49.50	99.75	188	2.5	3300	4,023	B	8/14/2001	
REMARKS: Houses Bionest BNC-1250 ATU											
01-011-64P-C4	C4	4.00	49.50	99.75	188	2.5	3300	4,023	D	8/12/2008	
REMARKS:											
01-011-64S-C4	C4	4.00	49.50	99.75	188	2.5	3300	4,023		8/14/2001	
REMARKS:											
01-011-65D-C4	C4	6.00	49.50	103.8	192	2.5	3300	4,023	B	10/31/2001	
REMARKS: Houses Bionest BNC-1250 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-65S-C4	C4	6.00	49.50	103.8	192	2.5	3300	4,023		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-66D-C3	C3	4.00	53.25	100.1	188.5	2.5	3500	4,461	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-66S-C3	C3	4.00	53.25	100.1	188.5	2.5	3500	4,461		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-67D-C4	C4	6.00	53.25	104.3	192.5	2.5	3500	4,461	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-67S-C4	C4	6.00	53.25	104.1	192.5	2.5	3500	4,461		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-68D-C3	C3	4.00	55.75	100.1	188.5	2.5	3700	4,461	B	8/14/2001	
REMARKS: Houses Bionest BNC-1500 ATU											



DEPARTMENT OF HEALTH
STATE HEALTH OFFICE
SEPTIC TANK DESIGNATED APPROVAL NUMBERS
SEPTIC TANK MANUFACTURERS
run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS		APPROVAL	
				WIDTH	LENGTH			(Pump Tanks)	USE	DATE	FAMILY
01-011-68S-C3	C3	4.00	55.75	100.1	188.5	2.5	3700	4,461		8/14/2001	
REMARKS:											
01-011-69D-C4	C4	6.00	55.75	104.1	192.5	2.5	3700	4,461	B	5/29/2002	
REMARKS: Houses Bionest BNC-1500 ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-69P-C4	C4	6.00	55.75	104.1	192.5	2.5	3700	4,461	D	2/28/2011	
REMARKS: ASSHTO HS20 traffic rating when buried between 18" to 48"											
01-011-69S-C4	C4	6.00	55.75	104.1	192.5	2.5	3700	4,461		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-70D-C3	C3	4.00	62.00	101.1	189.5	2.5	4150	5,107	B	4/9/2008	
REMARKS: 6" inlet and outlet.											
01-011-70P-C3	C3	4.00	62.00	101.1	189.5	2.5	4150	5,107	D	2/28/2011	
REMARKS: 6" inlet and outlet											
01-011-70S-C3	C3	4.00	62.00	101.1	189.5	2.5	4150	5,107		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-71D-C4	C4	6.00	62.00	105.1	193.4	2.5	4150	5,107	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-71P-C4	C4	6.00	62.00	105.1	193.4	2.5	4150	5,107	D	2/28/2011	
REMARKS: 6" inlet and outlet											
01-011-71S-C4	C4	6.00	62.00	105.1	193.4	2.5	4150	5,107		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-72D-C3	C3	4.00	64.00	101.1	189.5	3	4300	5,107	B	8/14/2001	
REMARKS:											
01-011-72P-C3	C3	4.00	64.00	101.1	189.5	3	4300	5,107	D	2/28/2011	
REMARKS:											
01-011-72S-C3	C3	4.00	64.00	101.1	189.5	3	4300	5,107		8/14/2001	
REMARKS:											
01-011-73D-C4	C4	6.00	64.00	105.1	193.5	3	4300	5,107		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-73P-C4	C4	6.00	64.00	105.1	193.5	3	4300	5,107	D	2/28/2011	
REMARKS: ASSHTO HS20 traffic rating when buried between 18" to 48"											
01-011-73S-C4	C4	6.00	64.00	105.1	193.5	3	4300	5,107		5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-74D-C4	C4	6.00	72.75	106	194.75	2.5	4900	5,910	B	4/9/2008	
REMARKS: 6" inlet and outlet											



DEPARTMENT OF HEALTH
STATE HEALTH OFFICE
SEPTIC TANK DESIGNATED APPROVAL NUMBERS
SEPTIC TANK MANUFACTURERS
run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS		APPROVAL DATE	FAMILY
				WIDTH	LENGTH			(Pump Tanks)	USE		
01-011-74P-C4	C4	6.00	72.75	106	194.75	2.5	4900	5,910	D	2/28/2011	
REMARKS: 6" inlet and outlet											
01-011-74S-C4	C4	6.00	72.75	109	194.75	2.5	4900	5,910		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-76D-C3	C3	4.00	73.50	102	190.75	2.75	5000	5,910	B	8/14/2001	
REMARKS:											
01-011-76P-C3	C3	4.00	73.50	102	190.75	2.75	5000	5,910	D	2/28/2011	
REMARKS:											
01-011-76S-C3	C3	4.00	73.50	102	190.75	2.75	5000	5,910		8/14/2001	
REMARKS:											
01-011-77D-C4	C4	6.00	73.50	106	194.75	2.75	5000	5,910	B	5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-77P-C4	C4	6.00	73.50	106	194.75	2.75	5000	5,910	D	2/28/2011	
REMARKS: ASSHTO HS20 traffic rating when buried between 18" to 48"											
01-011-77S-C4	C4	6.00	73.50	106	194.75	2.75	5000	5,910	B	5/29/2002	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-78D-C3	C3	4.00	71.50	102	190.75	2.5	4900	5,910	B	4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-78P-C3	C3	4.00	71.50	102	190.75	2.5	4900	5,910	D	2/28/2011	
REMARKS: 6" inlet and outlet											
01-011-78S-C3	C3	4.00	71.50	102	190.75	2.5	4900	5,910		4/9/2008	
REMARKS: 6" inlet and outlet											
01-011-90D-C4	C4	4.00	43.00	68.13	131.25	2.5	1250	1,500	B, GI	7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48" with 8" lid. Approved for GI use 5/22/2020											
01-011-90P-C4	C4	4.00	43.00	68.13	131.25	2.5	1250	1,500	D	2/28/2011	
REMARKS: lowered pass-through hole for dosing tank; AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-90S-C4	C4	4.00	43.00	68.13	131.13	2.5	1250	1,500		7/30/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-91D-C4	C4	6.00	43.00	72.1	135.25	2.5	1250	1,587	B, GI	10/31/2001	
REMARKS:											
01-011-91S-C4	C4	6.00	43.00	72.1	135.25	2.5	1250	1,587		10/31/2001	
REMARKS:											
01-011-92D-C4	C4	6.00	46.00	72.5	136.13	2.5	1350	1,688	B, GI	10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											



DEPARTMENT OF HEALTH
 STATE HEALTH OFFICE
 SEPTIC TANK DESIGNATED APPROVAL NUMBERS
 SEPTIC TANK MANUFACTURERS
 run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
 Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL DATE	FAMILY
				WIDTH	LENGTH			USE			
01-011-92P-C4	C4	6.00	46.00	72.5	136.13	2.5	1350	1,688	D	2/28/2011	
REMARKS: AASHTO HS20 TRAFFIC LOADING RATED WHEN BURIED BETWEEN 18" TO 48"											
01-011-92S-C4	C4	6.00	46.00	72.5	136.13	2.5	1350	1,688		10/31/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-93S-C4	C4	4.00	42.00	47.75	55.75	1	300	373		12/14/2001	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-94-C4	C4	4.00	34.75	47.75	55.75		300	358		6/8/2005	
REMARKS: Siphon tank.											
01-011-96S-C4	C4	3.00	42.00	45.75	53.75	1	300	370		1/31/2001	
REMARKS:											
01-011-97S-C4	C4	3.00	42.00	62.25	62.25	1	525	630		1/31/2001	
REMARKS:											
01-011-AK10-C3	C3	3.00	56.50	62	119	2	1342	1,583	ATU	8/12/2008	
REMARKS: Houses AquaKlear AK1000C 1000 gallon per day ATU (approval 8/12/2008); with pretreatment tank 01-011-02S-C4 and skimmer return through riser, houses 1000 gallon per day AquaKlear AK10S245C ATU (NSF245-certified) (approval 8/5/2019). two notches for 1/2" airline on inlet side											
01-011-AK5-C4	C4	3.00	49.50	50	89.5	1.5	640	773	ATU	12/14/2005	
REMARKS: Houses AquaKlear AK500C 500 gpd ATU; two notches for 1/2" airline on inlet side											
01-011-AK6S-C4	C4	3.00	50.50	50	139.5	2	1075	1,365	ATU	4/11/2019	
REMARKS: Monolithic baffles. Houses AquaKlear AK6S245C ATU (600 gal/day). NSF245 certified. Two notches for 1/2" airline and one notch for optional drip recirculation on inlet side											
01-011-AK8-C3	C3	3.00	57.75	57	103	2	1020	1,193	ATU	12/14/2005	
REMARKS: Used to house AquaKlear AK800C gallon per day ATU; two notches for 1/2" airline on inlet side.											
01-011-BM1-C3	C3	2.50	45.00	69.88	102	3	1100	1,479	ATU	10/31/2003	
REMARKS: Houses Bio-Microbics MicroFAST 0.5FS ATU (NSF 40-certified units only).											
01-011-BM10-C4	C4	6.00	63.00	82	158.5	2.5	2400	3,021		3/28/2012	
REMARKS: Converted 02-05-2012. Houses Bio-Microbics MicroFAST 1.5 ATU (NSF 40-certified units only).. AASHTO HS20 traffic loading rated when buried between 18" to 48".											
01-011-BM11-C4	C4	6.00	66.00	106	194.75	3	4500	5,909	ATU	3/28/2012	
REMARKS: Used to house Bio-Microbics MicroFAST 3.0F and 3.0FS ATU. AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-BM12-C4	C4	6.00	65.00	106	194.75	11	4400	5,913	ATU	3/28/2012	
REMARKS: AASHTO HS20 traffic loading rated when buried between 18" to 48". Used to house Bio-Microbics MicroFAST 4.5F ATU											
01-011-BM2-C4	C4	4.00	53.00	69	133	2.5	1500	1,919	ATU	10/31/2003	
REMARKS: Houses Bio-Microbics MicroFAST ATU. NSF 40-certified units: 0.5FS, 0.625FS, 0.75FS, 0.9.FS. NSF 245-certified units: 0.5FS, 0.625FS, 0.75FS.											
01-011-BM4-C3	C3	3.00	43.00	74.25	150.5	3	1600	2,433	ATU	10/31/2003	
REMARKS: Houses Bio-Microbics MicroFAST ATU. NSF 40-certified units: 0.5F, 0.625F, 0.75F, 0.9.F. NSF 245-certified units: 0.5F, 0.625F, 0.75F.											



DEPARTMENT OF HEALTH

STATE HEALTH OFFICE

SEPTIC TANK DESIGNATED APPROVAL NUMBERS

SEPTIC TANK MANUFACTURERS

run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	TOP EXTERIOR		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL GALLONS (Pump Tanks)		APPROVAL DATE	FAMILY
				WIDTH	LENGTH			USE			
01-011-BM5-C3	C3	4.00	66.00	102	190.75	3	4500	5,909	ATU	10/31/2003	
REMARKS: Used to house Bio-Microbics MicroFAST 3.0F and 3.0FS ATU											
01-011-BM6-C3	C3	4.00	65.00	102	190.75	11	4400	5,913	ATU	2/17/2004	
REMARKS: Used to house Bio-Microbics MicroFAST 4.5F ATU											
01-011-BM7-C4	C4	4.00	63.00	78	154.5	2.5	2400	3,021	ATU	9/13/2007	
REMARKS: Houses BioMicrobics MicroFAST 1.5 (F or S) ATU (NSF 40-certified units only). Inlet and/or outlet can be 4" or 6". Approved to house the BioMicrobics MicroFAST 0.9 ATU (NSF 245-certified units) 5/29/2020											
01-011-BM8-C4	C4	6.00	63.00	82	158.5	2.5	2400	3,021	ATU	3/1/2012	
REMARKS: (01-011-29S-C4 converted to ATU tank, 02-05-2012) Houses Bio-Microbics MicroFAST 1.5 ATU. NSF 40-certified units: with minimum 713 gallon pretreatment tank. NSF 245-certified units: with 1021 to 1613 gallon pretreatment tank.											
01-011-BM9-C4	C4	6.00	53.00	73	137	2.5	1500	1,919	ATU	10/31/2001	
REMARKS: Converted 01-011-27D-C4, Houses Bio-Microbics MicroFAST ATU. NSF 40-certified units: 0.5, 0.625, 0.75, 0.9. NSF 245-certified units: 0.5, 0.625, 0.75.. AASHTO HS20 traffic loading rated when buried between 18" to 48"											
01-011-E100-C4	C4	4.00	53.00	69	133	2.5	1500	1,920	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-23S-C4 Houses the Delta EcoPod E100-N (1,000 gpd). Minimum pretreatment tank effective capacity required is 1,000 gal; maximum allowed is 2,500 gal unless specified by the design engineer. The Delta EcoPod is NSF 245-certified.											
01-011-E150-C4	C4	4.00	60.00	77.25	153.5	2.5	2300	2,754	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-41S-C4 Houses the Delta EcoPod E150-N (1,500 gpd). Minimum pretreatment tank effective capacity required is 1,500 gal; maximum allowed is 3,750 gal unless specified by the design engineer. The Delta EcoPod is NSF 245-certified.											
01-011-E200-C4	C4	4.00	49.50	99.75	188	2.5	3300	4,000	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-64S-C4 Houses the Delta EcoPod E200-DCA (2,000 gpd) engineer-designed ATU. Minimum pretreatment tank effective capacity required is 2,000 gal.											
01-011-E250-C3	C3	4.00	55.75	100.1	188.5	2.5	3700	4,460	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-68S-C3, modified structural rib. Houses the Delta EcoPod E250-DCA (2,500 gpd) engineer-designed ATU. Minimum pretreatment tank effective capacity required is 2,500 gal.											
01-011-E300-C3	C3	4.00	64.00	101.1	189.5	3	4300	5,100	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-72S-C3 Houses the Delta EcoPod E300-DCA (3,000 gpd) engineer-designed ATU. Minimum pretreatment tank effective capacity required is 3,000 gal.											
01-011-E350-C3	C3	4.00	73.50	102	190.75	2.75	5000	5,900	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-76S-C3 Houses the Delta EcoPod E350-DCA (3,500 gpd) engineer-designed ATU. Minimum pretreatment tank effective capacity required is 3,500 gal.											
01-011-E400-C3	C3	4.00	73.50	102	190.75	2.75	5000	5,900	ATU	8/27/2020	
REMARKS: Originally approved as 01-011-76S-C3 Houses the Delta EcoPod E400-DCA (4,000 gpd) engineer-designed ATU. Minimum pretreatment tank effective capacity required is 4,000 gal.											
01-011-FT1-C3	C3	3.00	30.50	73.25	149.25	2.5	1150	1,505	Filter Me	7/29/2005	
REMARKS: Filter media tank w/65 sq ft surface area											
01-011-FT2-C4	C4	4.00	29.50	98.5	186.5	2.5	1950	2,648	Filter Me	1/3/2007	
REMARKS: Filter media tank w/112 sq ft surface area											



DEPARTMENT OF HEALTH
STATE HEALTH OFFICE
SEPTIC TANK DESIGNATED APPROVAL NUMBERS
SEPTIC TANK MANUFACTURERS
run date: 3/9/2021

Florida Septic, Inc.

Post Office Box 545
Hawthorne, FL 32640

Alachua

ACTIVE

TANK NUMBER	CATEGORY	WALL THICKNESS	LIQUID DEPTH	<u>TOP EXTERIOR</u>		IN-OUT DROP	EFFECTIVE GALLONS	TOTAL	APPROVAL	
				WIDTH	LENGTH			GALLONS (Pump Tanks)	USE	DATE
01-011-FT3-C4	C4	4.00	30.50	75.25	151.25	2.5	1150	1,505	Filter me	4/30/2007

REMARKS: Filter media tank w/65 sq ft surface area-corrected category to C4 on 01-26-2012