



**SIDE VIEW**

**END VIEW**

**TANK: CATEGORY 3.** 4" 4400 GALLON 2 COMPARTMENT TANK REINFORCED WITH FIBER AND #4 STEEL 12" O/C BOTH WAYS. 4" WALLS AND 4" BOTTOM. INLET AND OUTLET RESILIENT CONNECTORS PER ASTM-923-98. CONNECTORS MUST BE USED WITH APPROVED CLAMP. CONNECTOR WILL ACCEPT 4" PVC PIPE.

**LIDS:** 5" LID WITH 1-22" ROUND MANHOLE COVER AT EACH END OF TANK  
 8" LID WITH 1-22" ROUND MANHOLE COVER AT EACH END OF TANK  
 LID IS REINFORCED WITH GRADE 60 REBAR.

**TANK & LIDS:** 4000 PSI CONCRETE AT 28 DAYS

IMPRINTED ON INLET END OF TANK:

**LEGEND: FSI 4400 STATE APPROVAL NUMBER: 01-011-BM6-C3**

**WEIGHTS:** TANK ONLY 21,130  
 TANK & 5" LID 27,435  
 TANK & 8" LID 33,740

THIS TANK HOUSES THE 4.5 BIOMICROBICS FAST UNIT.

THIS SEWAGE TREATMENT RECEPACLE HAS BEEN DESIGNED, CONSTRUCTED AND STRUCTURALLY TESTED IN ACCORDANCE WITH CHAPTER 64E-6.013, FLORIDA ADMINISTRATIVE CODE, (FAC) DATED APRIL 28, 2010.

DRAWING NOT TO SCALE

HOUSES BIOMICROBICS  
 4.5 FAST

**FLORIDA SEPTIC, INC**

P.O. BOX 545  
 HAWTHORNE, FLORIDA 32640  
 (800) 940-8265

**MODEL:**

4" 4400 GALLON TANK

REVISED:  
 05/01/2011

APPROVAL DATE:  
 FEBRUARY 17, 2004